

# Wall mounting case AR-600



AR600 is the standard case for max. 16 REL/isp modules, ideal for medium size systems or multiple racks systems. AR600 systems are particularly suitable for small areas or on large sites, where it is preferable to have a number of small self-contained monitoring systems connected by a field bus to a remote Host system. AR600 is supplied fully wired, with one power unit up to 16 REL/isp modules and 24 ISP alarm outputs with (SPDT) relay rated at 3A 110 Vac.

## GENERAL SPECIFICATION

24 (SPDT) 3A 110 Vac relays outputs, configurable even with isp technology  
Standard serial line RS-485  
Extensive libraries of ready-to-go configuration for the logic of the alarms.

## Electrical Specification

Supply voltage	110-220 Vac
Supply fuse	1.6 A
Stabilised power supply output	13.75 or 27.5 Vdc
Overvoltage protection	± 50V.

## Environmental Specification

Storage temperature	-40 to 85 °C
Operating temperature	-10 to 70 °C
Humidity range	90% R.H. n.c.


## Mechanical Specification

Overall dimensions	600x600x400 mm
Mounting	3U-HE 19" Rack
Cabling	Screw terminals

## Part number description

AR600-x

└── n° unità bus



OGGIONI s.a.s. Via Gariberto da Besana, 11 20045 Besana Brianza (Mi)  
Tel. +39 0362 995062 Fax. +39 0362 540682 e-mail [oggionisas@tin.it](mailto:oggionisas@tin.it)  
On-line technical support [securnt@tin.it](mailto:securnt@tin.it) website: [www.oggionisas.com](http://www.oggionisas.com)